


Sound Control Underlay



QT provides exceptional performance under hard surface flooring and over concrete and wood joist construction.

TYPICAL CONSTRUCTION APPLICATION



USES

QT is compatible with a wide variety of floor finishes such as **ceramic tile, stone, hardwood, laminate and vinyl.** QT has proven performance ratings with many types of popular surfaces. Installation procedures of QT vary depending on the finished floor. For best results, speak to one of Wilrep Ltd.'s experienced sales technicians for installation instructions and technical information.

QT 4005 & 4010

QT 4005 & 4010 are affordable underlayments that effectively insulates against sound transfer between floors. Made from 100% recycled rubber and acrylic binders, this single-ply system is easy to install and offers performance higher than industry standards for impact sound reduction.

QT outperforms cork, polyethylene, fiberglass, and nylon matrix. New flooring can be installed directly on top of the standard 5 mm thick material. This means that no alterations have to be made to doors or thresholds.

QT is environmentally friendly. It will not rot, mildew or promote bacterial growth.

PRODUCT DATA

THICKNESS / WEIGHT

QT 4005 - 5 mm - 0.75 psf / 90 lbs. per roll<math>QT 4010 - 10 mm - 1.5 psf / 90 lbs. per roll

STANDARD DIMENSIONS

Available in Rolls,

QT 4005 - 48" wide X 30 ft. (120 sq. ft.)

QT 4010 – 48" wide X 15 ft. (60 sq. ft.)

QT 4005 (5 mm) is also available in half-rolls, 48" wide X 15 ft. (60 sq. ft.)

PERFORMANCE - AllC Ratings with QT

The chart below illustrates the QT Δ IIC contribution to a variety of floor constructions.

Floor Structure and Finish	Without QT	QT (21ΔIIC) 5 mm (3/16")	QT (25ΔIIC)10mm (3/8")
Bare 6" Concrete with Ceramic Tile	27	48	52
Bare 6" Concrete with Hardwood	27	51	55
Bare 6" Rein- forced Concrete with Ceramic Tile	32	53	57
Bare 8" Concrete With Hardwood	35	59	63

WILREP LTD.

1515 Matheson Blvd. E., Unit C-10, Mississauga, Ontario L4W 2P5

Tel.(905)625-8944 Fax (905)625-7142 www.wilrep.com e-mail: info@wilrep.com