


LEVELLING MOUNT




The standard for machinery levelling and isolation.



LEVEL-RITE® mounts have been engineered and tested to accommodate the needs of a broad spectrum of machinery. From small chip making mills to larger machining centers, Level-Rite mounts provide solutions for levelling, aligning and vibration isolation. They are built to meet industry's toughest demands and are virtually indestructible.

The rectangular shape of the Level-Rite Mount provides greater resistance to walking than circular mounts. This minimizes pad roll and entrapment of coolants and oils beneath the pad.

- ▶ Fast, accurate alignment.
- ▶ Accommodation of uneven floors.
- ▶ Increased equipment life.
- ▶ Prevents 'machine walking'
- ▶ Excellent isolation and shock performance.
- ▶ Simple fast installation.



SPECIFICATIONS

LEVEL-RITE MOUNT	A	L	W	H MIN./MAX.	STANDARD BOLT SIZE	MAX. MACH. FOOT TH.	MAX. LOAD (LBS.)
LR-2500	7.78	5.50	3.50	2.50/3.88	M12 X 1.75 X 150	2.27	2500
LR-5000	7.77	7.00	4.50	2.50/3.88	M16 X 2 X 150	2.08	5000
LR-7500	7.88	8.00	5.00	2.50/3.88	M20 X 1.5 X 150	1.91	7500
LR-12000	9.94	8.00	5.88	2.50/3.88	M24 X 2 X 200	3.65	12000
LR-16000	10.32	10.00	7.88	2.50/3.88	M24 X 2 X 200	3.40	16000
LR-25000	10.74	12.50	9.00	3.50/4.88	M30 X 2 X 200	3.53	25000
LR-35000	11.09	16.00	12.50	4.50/5.88	M36 X 2 X 250	4.52	35000

Dimensions are in inches except as shown.

UNISORB
INSTALLATION TECHNOLOGIES

Undercut hex. head
(for M30 and larger bolts)

External hex. head
(for M12 thru M24 bolts)

