

# Novibra® Type M


## VIBRATION ISOLATOR




A high degree of isolation and shock protection.

Type M is ideal for applications involving isolation of low frequency vibrations in all planes. The M Mount is also suitable for shock attenuation due to the ability to offer large deflections. This mount provides excellent vibration isolation for compressors, fans, pumps and electronic equipment.

**M7, M25, M50,  
M100, M200**



**M400, M600,  
M1500**



- ▶ Wide load rating options, 3.5 – 2500 kg.
- ▶ Corrosion protected to cope with arduous environments on land or marine applications (Fe/Zn 8C3 as per ISO 2081)
- ▶ Clear and durable product markings so that mountings can be identified after several years in operation.
- ▶ Not suitable for mobile use.

### SPECIFICATIONS

TYPE	DIMENSION IN mm								G Kg	WEIGHT Kg	M-MAX (Kg)	
	D	E	A	K	H	h	d	40° IRH			60° IRH	
M7	18	43	50	64	20	7	7.0	M6	0.02	3.5	9	
M25	33	56	66	85	25	11	8.0	M8	0.07	20	50	
M50	45	76	92	114	35	14	10.0	M10	0.16	40	80	
M100	53	96	110	136	40	15	11.5	M10	0.26	70	150	
M200	58	101	124	151	45	13	11.5	M10	0.42	130	220	
M400	78	—	120	150	63	18	14.5	M12	1.06	280	500	
M600	100	—	160	200	85	25	14.5	M16	2.35	380	750	
M1500	186	—	250	310	160	43	18.0	M24	9.43	1400	2500	

